



Ideas. Engineered.

Profilink Nolix

PVC window and door system

Sustainable solution for your future




Why choose Profilink NoLix?




Modern design

Straight and clean lines.



Glazing options

24 and 44 mm.



Choice of colours

Wide variety



High energy efficiency



Efficient solutions

Covers the highest
market requirements.

4.0

Quality

assured by latest
technologies in the
industry.



— KEEP YOUR HOME COSY

7-chamber profile construction provides excellent thermal transmittance of $U_f=1.1 \text{ W/m}^2 \text{ K}$

— MODERN DESIGN

Straight elegant silhouette gives excellent look of your windows.

— FORGET ABOUT CONDENSATION

With a glazing depth of 25 mm we almost completely eliminate the possibility of thermal bridging in the area of the spacers.

— SILENCE IS IMPORTANT

The ability to incorporate wide and special glazing panels in Profilink Nolix assures an effective noise protection.

— PROTECTION

The three levels of seal ensure a reliable barrier from temperature and weather influences.

— STATICS AND STABILITY

The design of steel reinforcements ensures long-lasting quality operation of the windows made with the system.

— 82 mm INSTALLATION WIDTH

Designed for maximum comfort and energy efficiency of buildings.

— EASY MAINTENANCE

No need for periodic painting. The windows only require quick and easy cleaning of the profiles.

COLOUR OPTIONS



White



Anthracite



Golden Oak



Nussbaum



Profilink
by **LINKIN**

www.profilink.eu

